SM-14 HYDRAULIC MICRODRILLING RIG



YEAR OF MANUFACTURE SERIAL NUMBER CONFIGURATION PRICE

2010 869 Rotary & CFA £POA Ex Works, UK

The SM-14 drilling rig is a multipurpose drilling rig. Its modular design is engineered for the execution of micro piles, tie-backs, jet-grouting, coring, CFA, drain and water wells.

SPECIFICATION:

- Undercarriage width 2300mm. Track width 400mm.
- Weight 13500kg.
- 50-415mm clamp and breaker.
- Mast stroke: 4m.
- Max. hoist 89kN. Max. feed force: 45kN.
- Service winch: 20 kN
- Rotary HR-12, Max. torque: 12kNm, Max speed: 221rpm.
- 3 ½ " API Reg Accessories.
- Double emergency tag lines, safety guard with slow rotation.





OPTIONAL ITEMS FOR CFA.

- HTD250G CFA Rotary, Max. torque: 25kNm, Max speed: 52rpm.
- 4" Swivel
- 4" Swan neck



Steph Keane – Micro Piling Sales Manager

Phone: 0044 (0)1832 274602 Fax: 0044 (0)1832 274677 Mobile: 0044 (0)7900 926372 E-mail:steph@soilmec.co.uk